




Thimble ion chambers ,0.13 cm³



- Vented through waterproof sleeve
- Fully guarded
- Supplied with a ⁶⁰Co factor calibration certificate ($N_{D,w}:N_k:H_{D,a}=N_{gas}$) traceable to PTB

For absolute dose measurements, depth dose measurements and field profile analysis in a water-phantom or free-air.

It is waterproof, vented chamber suitable for electron and photon beam dosimetry. Rugged Shonka plastic material provides increased durability.

SPECIFICATIONS:

Material:

Outer electrode: Shonka C552 / 1.7 g/cm³

Inner electrode: Shonka C552 / 1.7 g/cm³

Connector type: BNC triaxial

Cable length: 1.3 cm

Operation:

Typical leakage: $\pm 4 \times 10^{-15}$ A

Radiation quality: 100kV to 50 MeV

Calibration factor (nominal) $N_{D,w} = 260$ mGy/nC

Dimensions:

Active volume: 0.13 cm³

Total active length: 5.8 mm

Cylinder length: 2.8 mm

Inner diameter of outer electrode: 6 mm

Thickness of outer electrode: 0.4 mm

Diameter of inner electrode: 1.0 mm

Length of inner electrode: 3.3 mm

Model: EW 30-744

© Elimpex-Medizintechnik, Spechtgasse 32, A-2340 Moedling, Austria
phone +43-2236-410450
fax +43-2236-410459

